

A Hybrid DWT-SVD Based Digital Image Watermarking Algorithm for Copyright Protection

Shuchi Sirmour¹, Archana Tiwari²

¹Assistant Professor, ²Associate Professor

^{1,2}Department of Electronics and Instrumentation Engineering

^{1,2}Chhatrapati Shivaji Institute of Technology, Durg

Abstract - Digital watermarking is the process of embedding information into a digital signal. In this paper to improve the robustness, the hybrid DWT-SVD based algorithm is proposed for embedding and extracting process. The suggested method is performed by modification on singular value decomposition of images in Discrete Wavelet Transform (DWT) domain. Modification of the appropriate sub-bands leads to a watermarking scheme which favorably preserves the quality. The experimental result shows good robustness by using hybrid DWT-SVD method in comparison with DWT based watermarking algorithm using Haar wavelet.

Keywords – Digital watermarking, Discrete wavelet transform (DWT), Singular value decomposition (SVD).

I. INTRODUCTION

In recent years, the accessing of multimedia or digital data has become very easy because of the fast development of the internet. In other words, this development makes unauthorized, illegal access and manipulation of multimedia files over internet. Watermarking is a branch of information hiding which is used to hide proprietary information in digital media like photographs, digital music, or digital video. The ease with which digital content can be exchanged over the internet has created copyright infringement issues. Copyrighted material can be easily exchanged over peer-to-peer networks and this has caused major concerns to those content providers who produce these digital contents [1]. Digital watermark is a code that is embedded inside an image. It acts as a digital signature, giving the image a sense of ownership or authenticity. Digital watermarking stands for embedding a signal, called

‘watermark’ into a digital cover, in order to prove ownership, authenticity or integrity of the cover or it may relate to audio, images, video or even text. Digital watermarking provides copyright protection of data. For image watermarking, the algorithms can be categorized into one of the two domains: spatial domain or transform domain [2,3]. In spatial domain the data is embedded directly by modifying pixel values of the host image, while transform domain schemes embed data by modifying transform domain coefficients. Algorithm used for spatial domain are less robust for various attacks as the changes are made at Least Significant Substitution (LSB) of original data. While in the transform domain the watermark is embedded by changing the magnitude of coefficients in a transform domain with the help of discrete cosine transform (DCT), discrete Fourier transform (DFT), discrete wavelet transform (DWT), and singular value decomposition (SVD) techniques [4,5]. This provide most robust algorithm for many common attacks.

II. DWT AND SVD

A. Discrete Wavelet Transform(DWT)

The Discrete Wavelet Transform(DWT) is currently used in a wide variety of signal processing applications, such as in audio and video compression, removal of noise in audio and the simulation of wireless antenna distribution. Wavelets have their energy concentrated in time and are well suited for the analysis of transient, time-varying signals [6]. Wavelet transform use wavelet filters to transform the image. There are many available filters, although the most commonly used filters for watermarking are Haar Wavelet Filter, Daubechies Orthogonal Filters and Daubechies Bi- Orthogonal Filters. Each of these filters decomposes the image into several frequencies.

DWT involves decomposition of image into frequency channel of constant bandwidth. This causes the similarity of available decomposition is done in multistage transformation. At level 1: image is decomposed into four sub-bands: lower (LL), vertical (LH), horizontal (HL), and diagonal (HH) detail components. Where LL denotes the coarse level coefficient which is the low frequency part of the image. LH, HL, and HH denote the finest scale wavelet coefficient. The LL sub-band can be decomposed further to obtain higher level of decomposition. This decomposition can continue until the desired level of decomposition is achieved for the application. The watermark can also be embedded in the remaining three sub-bands to maintain the quality of image as the LL sub-band is more sensitive to human eye.

B. Singular Value Decomposition (SVD)

An image can be represented as a matrix of positive scalar values. Formally, SVD for any image say A of size $m \times m$ is a factorization of the form given by $A = USV^T$, where U and V are orthogonal matrices in which columns of U are left singular vectors and columns of V are right singular vectors of image A. S is a diagonal matrix of singular values in decreasing order. The basic idea behind SVD technique of watermarking is to find SVD of image and the altering the singular value to embed the watermark. In digital watermarking schemes, SVD is used due to its main properties: 1) A small agitation added in the image, does not cause large variation in its singular values. 2) The singular value represents intrinsic algebraic image properties [4].

III. PROPOSED ALGORITHM

The image decomposition is done with “Haar” which is symmetric, simple and orthogonal wavelet. The SVD is then applied to a selected subband. This result in three matrices U, S and V. We assume the dimension of the cover image I is $N \times N$.

A. Embedding Watermark

- Read the cover image of size and the watermark of the same size.
- Use Haar DWT to decompose the image into four sub bands i.e. (LL, LH, HL, HH)
- Apply SVD to LH sub-band i.e.

$$I_o = U_o S_o V_o^T$$

Where $I_o = LH$

- Insert the watermark image into the middle component of the SVD applied cover image as in above equation:

$$W = U_w S_w V_w^T$$

Where W = watermark

- Apply inverse SVD (ISVD) to the LH sub-band by multiplying the modified matrix S_{ow} with the orthogonal matrices.
- Apply inverse DWT (IDWT) to get the watermarked image.

B. Watermark Extraction

- Read the watermarked image.
- Apply Haar DWT to decompose the watermarked image into four sub-bands i.e. (LL, LH, HL, HH)
- Apply SVD to LH sub-band i.e.

$$I_{ow} = U_{ow} S_{ow} V_{ow}^T$$

Where $I_{ow} = LH$

- The matrix as the middle component of the SVD that includes the watermark is computed and the watermark is extracted using the original image as it is a non-blind watermarking method.
- Apply inverse SVD to the LH sub-band.
- Perform inverse DWT method.
- The extracted watermark is recovered.

IV. Performance Evaluation

A. Imperceptibility

Imperceptibility is the perceived quality of the host image that should not be distorted by the presence of the watermark. For quantitative evaluation of a watermarked image, the Peak Signal-to-Noise Ratio (PSNR) is typically used to evaluate the performance of the proposed scheme, which is defined as:

$$PSNR = 10 \log_{10} (255/MSE)^2 \text{ dB}$$

$$MSE = \sum_{i=0}^{n-1} \sum_{j=0}^{m-1} \frac{(a_{ij} - b_{ij})^2}{n * m}$$

Where $m \times n$ is the image size, a_{ij} and b_{ij} are the corresponding pixel values of two images [8].

V. EXPERIMENTAL RESULTS

To demonstrate the proposed approach, Lena's image is used as an original image and copy-right image is used as the watermark. Figure:1 shows the cover image of size 512 x 512. Figure:2 shows the watermark image of size 340 x 340. Figure:3 shows the watermarked image. Figure:4 shows the recovered watermark image.

The peak signal-to-noise ratio (PSNR) was used as a measure of the quality of a watermarked image.



Figure: 3 Watermarked Image



Figure: 1 Original Image



Figure: 4 Recovered Watermark Image



Figure: 2 Watermark Image

Table 1 : Experimental Data

Original Image	Watermark Image	MSE	PSNR
Lena Image	Copy right image	0.0230	64.5199
Lena Image	Mission completed image	0.0268	63.8425

Table 1 shows the peak signal to noise ratio of performance of our proposed method of original image with various watermark image, where our watermarked images PSNR has a better performance than others.

VI. CONCLUSION

Watermarking is an information hiding technique where a secret message is concealed in the digital content. In order to make this hidden information secure, imperceptible and robust, the watermark should be embedded in some proper locations. Improving the security aspect of the watermarking system, without any cost of imperceptibility and robustness, is one of the challenges of today's research in watermarking.

In our simulation we go through the numerous tests on original image with size 512 x 512. In our proposed method, PSNR of watermark images values are high as compare to other papers. The experimental results have confirmed that this new technique has two properties high fidelity and robustness.

REFERENCES

- [1] Robert, L., and T. Shanmugapriya. "A study on digital watermarking techniques." *International Journal of Recent Trends in Engineering*, Vol. 1, no. 2, pp.223-225, 2009
- [2] Reddy, R., M. V. N. Prasad, and D. S. Rao. "Robust Digital Watermarking of Images using Wavelets." *International Journal of Computer and Electrical Engineering*, vol.1, no.2, pp.1793-8163, 2009
- [3] Sang, Jun, and Mohammad S. Alam. "Fragility and robustness of binary-phase-only-filter-based fragile/semifragile digital image watermarking." *Instrumentation and Measurement, IEEE Transactions*, vol. 57, no.3, pp. 595-606, 2008
- [4] Liu, Ruizhen, and Tieniu Tan. "An SVD-based watermarking scheme for protecting rightful ownership." *Multimedia, IEEE Transactions*, vol. 4, no.1, pp.121-128, 2002.
- [5] Nikolaidis, Athanasios, and Ioannis Pitas. "Asymptotically optimal detection for additive watermarking in the DCT and DWT domains." *Image Processing, IEEE Transactions*, vol.12, no.5, pp. 563-571, 2003
- [6] Kaur, Manpreet, Sonika Jindal, and Sunny Behal. "A Study of Digital Image Watermarking." *Journal of Research in Engineering and Applied Sciences*, vol. 2,no.2, pp. 126-136, 2012
- [7] Singh, Dharm, Naveen Choudhary, and Madhuri Agrawal. "Scrambled hybrid wavelet-singular domain digital image watermarking." *Software Engineering (CONSEG), CSI Sixth International Conference on. IEEE*, 2012
- [8] Arya, Meenakshi S., Rajesh Siddavatam, and S. P. Ghreera. "A hybrid semi-blind digital image watermarking technique using lifting wavelet transform—Singular value decomposition." *Electro/Information Technology (EIT), IEEE*, pp.1-6, 2011.
- [9] Seema and Sharma Sheetal. "DWT-SVD Based Efficient Image Watermarking Algorithm to Achieve High Robustness and Perceptual Quality", *International Journal of Advanced Research in Computer Science and Software Engineering*, vol. 2, Issue 4, 2012.